

## DRYER DATA SHEET Refrigerant Dryers

MODEL DATA				
1	Manufacturer	ZEKS		
2	Date	12/29/16		
3	Model Number	200HSGA400		
4	Cycling/Non-Cycling	Cycling		
5	Refrigerant Type	R-404A		
	DESCRIPTION	FULL FLOW	10% FLOW	UNITS
6	Tested Flow	200	20	scfm <sup>b</sup>
7	Outlet Pressure Dewpoint	40.5	40.5	°F
8	Pressure Drop	2.8	0.7	psi(d)
9	Total Dryer Input Power	2.1	.63	kW
10	Specific Package Power <sup>c</sup>	1.05	3.15	kW/100 scfm

## Notes:

a. Dryer ratings at the following inlet conditions to the dryer (as per ISO 7183, Table 2, Option A2):

Inlet Compressed Air Temperature: 100°F (38°C)
Inlet Compressed Air Pressure: 100 psig (7 Bar)
Max. Ambient Air Temperature: 100°F (38°C)
Inlet Compressed Air Relative Humidity 100% (Saturated)

- b. SCFM defined as the volume of free air in cubic feet per minute measured at 14.5 psia (1.0 Bar), 68°F (20°C) temperature and 0% R.H. (0 WVP).
- c. (Total Dryer Input Power/tested flow) x 100

Member



This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.

Consult the CAGI website, <u>www.cagi.org</u>, for a list of participants in the third party verification program.