

## DRYER DATA SHEET Refrigerant Dryers

MODEL DATA						
1	Manufacturer	ZEKS				
2	Date	5/31/11				
3	Model Number	300HSGW400				
4	Cycling/Non-Cycling	CYCLING				
5	Refrigerant Type	R-404A				
	DESCRIPTION	FULL FLOW	10% FLOW	UNITS		
6	Tested Flow	300	30	scfm <sup>b</sup>		
7	Outlet Pressure Dewpoint	39	39	°F		
8	Pressure Drop	2.1	.1	psi(d)		
9	Total Dryer Input Power	1.70	.28	kW		
10	Specific Package Power <sup>c</sup>	.57	.93	kW/100 scfm		

Notes:

a. Dryer ratings at the following inlet conditions to the dryer (as per ISO 7183, Table 2, Option A2):

•	Inlet Compressed Air Temperature:	100°F (38°C)
•	Inlet Compressed Air Pressure:	100 psig (7 Bar)
•	Max. Ambient Air Temperature:	100°F (38°C)
•	Inlet Compressed Air Relative Humidity	100% (Saturated)

- b. SCFM defined as the volume of free air in cubic feet per minute measured at 14.5 psia (1.0 Bar), 68°F (20°C) temperature and 0% R.H. (0 WVP).
- c. (Total Dryer Input Power/tested flow) x 100



This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.

Consult the CAGI website, <u>www.cagi.org</u>, for a list of participants in the third party verification program.